



L A S E R - G

(250 WATT MAX.)



SIDE VIEW



TOP VIEW



BF



FB



BB



FF



NF



FN

SPECIFICATIONS

HOUSING: PRECISE CORROSION RESISTANT, DURABLE CAST ALUMINUM CONSTRUCTION.

OPTICS: TEMPERED GLASS TO PROVIDE LASER BEAM IN ONE DIRECTION AND GENERAL ILLUMINATION IN THE OTHER DIRECTION.

LAMP HOLDER: H.I.D.-MEDIUM BASE PORCELAIN.
QUARTZ-MINI CAN FOR TUNGSTEN HALOGEN SINGLE ENDED LAMP.

LAMP: (BY OTHERS)




BALLAST: H.P.F./C.W.A. AUTOTRANSFORMER. -20° STARTING TEMPERATURE. ELECTRICAL COMPONENTS ARE MOUNTED TO A REMOVABLE BALLAST TRAY.

MOUNTING: WALL MOUNT, COLUMN MOUNT.


FINISH: POLYESTER POWDER COAT-STATE OF THE ART 20 PSI PRESSURE POWER WASH AT 140° TEMPERATURE INCORPORATES FOUR STEP IRON PHOSPHATE PROCESS TO CLEANSE AND PRETREAT THE METAL SURFACE FOR MAXIMUM PAINT ADHESION. ELECTROSTATICALLY APPLIED TEXTURED POLYESTER POWDER TOPCOAT IS BAKED AT 400° TEMPERATURE FOR MAXIMUM HARDNESS AND EXTERIOR DURABILITY.




LAS-G
[250 WATT MAX.]




BF




FB




BB



FF



NF



FN

ORDERING INFORMATION

MODEL NO. :	WATTAGE TYPE VOLTAGE	FINISH	OPTIONS																								
LAS-G																											
MODEL NO. :	LAMP	FINISH	OPTIONS																								
LAS-G	<table border="0"> <tr> <th>WATTAGE</th> <th>TYPE</th> <th>VOLTAGE</th> </tr> <tr> <td><input type="checkbox"/> 250</td> <td><input type="checkbox"/> HPS</td> <td><input type="checkbox"/> 120</td> </tr> <tr> <td><input type="checkbox"/> 175</td> <td><input type="checkbox"/> MH</td> <td><input type="checkbox"/> 208</td> </tr> <tr> <td><input type="checkbox"/> 150</td> <td><input type="checkbox"/> MV</td> <td><input type="checkbox"/> 240</td> </tr> <tr> <td><input type="checkbox"/> 100</td> <td><input type="checkbox"/> QUARTZ HALOGEN</td> <td><input type="checkbox"/> 277</td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> 480</td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> MT</td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> OTHER</td> </tr> </table>	WATTAGE	TYPE	VOLTAGE	<input type="checkbox"/> 250	<input type="checkbox"/> HPS	<input type="checkbox"/> 120	<input type="checkbox"/> 175	<input type="checkbox"/> MH	<input type="checkbox"/> 208	<input type="checkbox"/> 150	<input type="checkbox"/> MV	<input type="checkbox"/> 240	<input type="checkbox"/> 100	<input type="checkbox"/> QUARTZ HALOGEN	<input type="checkbox"/> 277			<input type="checkbox"/> 480			<input type="checkbox"/> MT			<input type="checkbox"/> OTHER	STANDARD TEXTURED FINISH <input type="checkbox"/> BLACK RAL-9005-T <input type="checkbox"/> WHITE RAL-9003-T <input type="checkbox"/> GREY RAL-7004-T <input type="checkbox"/> DRK BRONZE RAL-8019-T <input type="checkbox"/> GREEN RAL-6005-T <small>FOR SMOOTH FINISH REMOVE SUFFIX "T" (EXAMPLE: RAL-9500) SEE WEBSITE FOR ADDITIONAL COLORS</small>	<input type="checkbox"/> BEAM UP, FLOOD DOWN..... BF <input type="checkbox"/> FLOOD UP, BEAM DOWN..... FB <input type="checkbox"/> BEAM UP, BEAM DOWN..... BB <input type="checkbox"/> FLOOD UP, FLOOD DOWN..... FF <input type="checkbox"/> NO UP LIGHT, FLOOD DOWN..... NF <input type="checkbox"/> FLOOD UP, NO DOWN LIGHT... FN
	WATTAGE	TYPE	VOLTAGE																								
<input type="checkbox"/> 250	<input type="checkbox"/> HPS	<input type="checkbox"/> 120																									
<input type="checkbox"/> 175	<input type="checkbox"/> MH	<input type="checkbox"/> 208																									
<input type="checkbox"/> 150	<input type="checkbox"/> MV	<input type="checkbox"/> 240																									
<input type="checkbox"/> 100	<input type="checkbox"/> QUARTZ HALOGEN	<input type="checkbox"/> 277																									
		<input type="checkbox"/> 480																									
		<input type="checkbox"/> MT																									
		<input type="checkbox"/> OTHER																									
	NOTES: QUARTZ HALOGEN UNITS - MAX. 150 WATTS																										