

SPECIFICATIONS

HOUSING: PRECISE, ROUND CORNER CAST ALUMINUM CONSTRUCTION.

LENS ASS'Y: PRECISE, DURABLE CAST ALUMINUM DOOR FRAME SURROUNDS 3/16" CLEAR TEMPERED GLASS LENS. GLASS IS SEALED TO DOOR WITH HIGH TEMPERATURE SILICONE SEAL.

OPTICS: PRECISION SEGMENTED FLOOD LIGHTING OPTICS. NARROW, MEDIUM AND WIDE BEAM DISTRIBUTION FOR BOTH POLE AND WALL MOUNT APPLICATION 400 WATT MAX LAMP SIZE

GASKETING: CLOSED CELL EPDM GASKETING COMPRESSED BETWEEN DOOR AND HOUSING SEALS OPTICAL CHAMBER.



LAMP HOLDER: MOGUL BASE PORCELAIN.

LAMP: (BY OTHERS)

BALLAST: H.P.F./C.W.A. AUTOTRANSFORMER. -20° STARTING TEMPERATURE.






FINISH: POLYESTER POWDER COAT-STATE OF THE ART 20 PSI PRESSURE POWER WASH AT 140° TEMPERATURE INCORPORATES FOUR STEP IRON PHOSPHATE PROCESS TO CLEANSE AND PRETREAT THE METAL SURFACE FOR MAXIMUM PAINT ADHESION. ELECTROSTATICALLY APPLIED TEXTURED POLYESTER POWDER TOP COAT IS BAKED AT 400° TEMPERATURE FOR MAXIMUM HARDNESS AND EXTERIOR DURABILITY.

FLOOD MOUNT



ORDERING INFORMATION

MODEL NO.:	OPTICS	WATTAGE TYPE VOLTAGE	MOUNTING	FINISH	OPTIONS
LUM-FLD					

MODEL NO.:	OPTICS	LAMP	MOUNTING	FINISH	OPTIONS	
L U M - F L D	<input type="checkbox"/> WIDE FLOOD WFL.... 	<input type="checkbox"/> 400 <input type="checkbox"/> HPS <input type="checkbox"/> 120 <input type="checkbox"/> 250 <input type="checkbox"/> MH <input type="checkbox"/> 208 <input type="checkbox"/> 200 <input type="checkbox"/> MV <input type="checkbox"/> 240 <input type="checkbox"/> 175 <input type="checkbox"/> 277 <input type="checkbox"/> 150 <input type="checkbox"/> 480 <input type="checkbox"/> 100 <input type="checkbox"/> MT	 <input type="checkbox"/> ADJUSTABLE KNUCKLE FITTER (NKLE27)	STANDARD TEXTURED FINISH <input type="checkbox"/> BLACK RAL-9005-T <input type="checkbox"/> WHITE RAL-9003-T <input type="checkbox"/> GREY RAL-7004-T <input type="checkbox"/> DRK BRONZE RAL-8019-T <input type="checkbox"/> GREEN RAL-6005-T	<input type="checkbox"/> CLEAR POLYCARBONATE DIFFUSER.....LEX <input type="checkbox"/> PHOTO CELL + VOLTAGE (EXAMPLE: PC120V).....PC+V <input type="checkbox"/> TWIST LOCK PHOTO CELL+VOLTAGE (EXAMPLE TPC120V).....TPC+V <input type="checkbox"/> TWIST LOCK RECEPTACLE ONLY.....TPR <input type="checkbox"/> SINGLE FUSE (120V., 277V).....SF <input type="checkbox"/> DOUBLE FUSE (208V., 240V).....DF	
	<input type="checkbox"/> MEDIUM FLOOD MFL.... 			 <input type="checkbox"/> ADJUSTABLE KNUCKLE FITTER (NKLE23)	FOR SMOOTH FINISH REMOVE SUFFIX "T" (EXAMPLE: RAL-9500) SEE WEBSITE FOR ADDITIONAL COLORS	
	<input type="checkbox"/> NARROW FLOOD NFL.... 					
			METAL HALIDE UNITS ONLY USE ED28 LAMP FOR 400 W. USE MEDIUM BASE LAMP FOR 100 W.			