#### PROJECT TYPE:

# XAO MINI

### **FEATURES**


#### Δrm

Durable corrosion resistant, cast aluminum construction.


#### **Finish**

Super TGIC polyester powder coating is applied onto a metal substrate this has been pretreated with a four-stage process for maximum adhesion and color retention. The top coat is baked at 400° F for maximum hardness and exterior durability.






**XAOM-PM-2-180** EPA = 1.20



**XAOM-PM-1** EPA = 0.75



XAOM-PM-WM


SCALE: 1/2"=1'






#### **SPECIFICATIONS**


## Trulevel System® Assembly



1. Loosen (4) Captive Screws and remove Access Door from Trulevel Coupler, pull out Quick Connect from Trulevel Coupler and Trulevel Ball.




- 2. Place Trulevel Ball inside of Trulevel Coupler as illustrated
  - A Notched Section of Trulevel Ball must face outward as illustrated.
  - B Flat Section of Trulevel Ball must face inward.



 ${\bf 3.} \ \ {\bf Connect \ Quick \ Connect \ components, \ push \ components \ inside \ of \ Trulevel$ Coupler cavity, replace Access Door and loosely secure, do not tighten.

Fixture will suspend without Access Door during installation.



4. Rotate (left to right  $\pm$  22.5°) and level Luminaire to desired position. Tighten Access Door.

(Tighten each bolt to recommended torque: 10 ft-lb, foot-pound)

Trulevel Pendant Mount is intended to allow for fixture leveling, but is not intended to be "free-swinging" upon proper installation.

## **ORDERING INFORMATION**

Spec/Order Example: XAOM-PM-5-90/RAL-7004-T



Consult factory for custom colors



