

TECHNICAL DATA - VLED - ARM MOUNT#2 (SMALL)

LUMENS - BUG RATINGS - INPUT WATTAGE (4000K CCT)

EX: TSU-M-64VLED

COMPATIBILITY LIST: *TSUM *TSUW	NUMBER OF LEDs	64									
	DRIVE CURRENT (mA)	350			525			N/A			
	INPUT WATTAGE (W)	68			100			N/A			
DISTRIBUTION											
	LUMENS	LPW	BUG RATING		LUMENS	LPW	BUG RATING		LUMENS	LPW	BUG RATING
II	6,647	98	B 2	U 0 G 2	9,351	94	B 2	U 0 G 2	N/A	N/A	N/A
III	6,564	97	B 1	U 0 G 2	9,234	92	B 2	U 0 G 2	N/A	N/A	N/A
IV	6,411	94	B 1	U 0 G 2	9,019	90	B 2	U 0 G 2	N/A	N/A	N/A
V-SQ	7,196	106	B 3	U 0 G 1	10,074	101	B 3	U 0 G 2	N/A	N/A	N/A
HOUSE-SIDE SHIELD OPTION											
II-HS	5,053	74	B 1	U 0 G 2	7,109	71	B 2	U 0 G 2	N/A	N/A	N/A
III-HS	5,037	74	B 1	U 0 G 2	7,087	71	B 1	U 0 G 2	N/A	N/A	N/A
IV-HS	4,867	72	B 1	U 0 G 2	6,847	68	B 1	U 0 G 2	N/A	N/A	N/A

*Not available in 700mA Drive Current

EX: TSU-M-48VLED

COMPATIBILITY LIST: TSUM *AERM *TSUW	NUMBER OF LEDs	48													
	DRIVE CURRENT (mA)	350		525		700									
	INPUT WATTAGE (W)	54		78		104									
	DISTRIBUTION														
	LUMENS	LPW	BUG RATING		LUMENS	LPW	BUG RATING		LUMENS	LPW	BUG RATING				
II	5,364	99	B 1	U 0	G 2	7,426	95	B 2	U 0	G 2	9,298	89	B 2	U 0	G 2
III	5,297	98	B 1	U 0	G 2	7,333	94	B 1	U 0	G 2	9,181	88	B 2	U 0	G 2
IV	5,174	96	B 1	U 0	G 2	7,163	92	B 1	U 0	G 2	8,967	86	B 1	U 0	G 2
V-SQ	5,807	108	B 3	U 0	G 1	8,000	103	B 3	U 0	G 1	10,016	96	B 3	U 0	G 2
HOUSE-SIDE SHIELD OPTION															
II-HS	4,078	76	B 1	U 0	G 1	5,645	72	B 1	U 0	G 2	7,067	68	B 2	U 0	G 2
III-HS	4,065	75	B 1	U 0	G 2	5,628	72	B 1	U 0	G 2	7,047	68	B 1	U 0	G 2
IV-HS	3,927	73	B 1	U 0	G 2	5,438	70	B 1	U 0	G 2	6,808	65	B 1	U 0	G 2

*Not available in 700mA Drive Current

EX: MLX-T-24VLED (DOWNLIGHT OPTION ONLY)

COMPATIBILITY LIST: *MLXT	NUMBER OF LEDs	24								
	DRIVE CURRENT (mA)	350			525			700		
	INPUT WATTAGE (W)	27			39			N/A		
DISTRIBUTION										
	LUMENS	LPW	BUG RATING			LUMENS	LPW	BUG RATING		
II	2,684	99	B 1 U 0 G 1			3,713	95	B 1 U 0 G 1		
III	2,650	98	B 1 U 0 G 1			3,667	94	B 1 U 0 G 1		
IV	2,589	96	B 1 U 0 G 1			3,581	92	B 1 U 0 G 1		
HOUSE-SIDE SHIELD OPTION										
II-HS	2,037	75	B 1 U 0 G 1			2,822	72	B 1 U 0 G 1		
III-HS	2,035	75	B 0 U 0 G 1			2,814	72	B 1 U 0 G 1		
IV-HS	1,965	73	B 0 U 0 G 1			2,719	70	B 0 U 0 G 1		

*Not available in 700mA Drive Current