

TENON MOUNTED ARM

XAD

PROJECT NAME: _____

PROJECT TYPE: _____

FEATURES

Arm

Durable corrosion resistant, cast aluminum construction.


Finish

Electrostatically applied TGIC Polyester Powder Coat on substrate prepared with 20 PSI power wash at 140°F. Four step media blast and iron phosphate pretreatment for protection and paint adhesion. 400°F bake for maximum hardness and durability.




XAD


Patent pending



XAD-2-180
EPA = 1.68



XAD-1
EPA = 1.02









XAD-WM
EPA = 0.79

SCALE: 1/2"=1'

ORDERING INFORMATION

Spec/Order Example: XAD-3-180/RAL-9003-S

Configuration	<input type="checkbox"/>  XAD-WM	<input type="checkbox"/>  XAD-1	<input type="checkbox"/>  XAD-2-180	<input type="checkbox"/>  XAD-3-180	<input type="checkbox"/>  XAD-4-90	<input type="checkbox"/>  XAD-5-90
Finish*	<input type="checkbox"/> Black RAL-9005-T	<input type="checkbox"/> White RAL-9003-T	<input type="checkbox"/> Grey RAL-7004-T	<input type="checkbox"/> Dark Bronze RAL-8019-T	<input type="checkbox"/> Green RAL-6005-T	<p>*Standard texture finish</p> <p>For smooth finish replace suffix "T" with suffix "S" (Example: RAL-9005-S)</p> <p>Consult factory for custom colors</p>